

# SAFETY DATA SHEET

Issuing Date 27-Apr-2007

Revision Date 26-Dec-2013

Revision Number 0

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

**Product Name** Rust Rustler Aluminum Paint

### Other means of identification

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Rust preventative

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Rust Rustler Paint Products  
P.O. Box 28, Greenville, Texas, 75403-0028 US

Phone: 903-455-4576

Contact: Tim Stainback

Contact Phone: 903-455-4576

Emergency Phone: 903-455-4576

### Emergency telephone number

**Company Emergency Phone Number** 903-455-4576

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

|   |             |
|---|-------------|
| Acute toxicity - Inhalation (Gases)       | Category 4  |
| Acute toxicity - Inhalation (Dusts/Mists) | Category 4  |
| Skin corrosion/irritation                 | Category 2  |
| Germ cell mutagenicity                    | Category 1B |
| Carcinogenicity                           | Category 2  |
| Aspiration toxicity                       | Category 1  |
| Flammable liquids                         | Category 3  |

### GHS Label elements, including precautionary statements

#### Emergency Overview

#### Signal word

Danger

#### Hazard statements

Harmful if inhaled  
 Causes skin irritation  
 May cause genetic defects  
 Suspected of causing cancer  
 May be fatal if swallowed and enters airways  
 Flammable liquid and vapor



**Appearance** Silver

**Physical State** Liquid

**Odor** Solvent

---

**Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Wash face, hands and any exposed skin thoroughly after handling  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting/equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
Specific treatment (see supplemental first aid instructions on this label)

**Skin**

If skin irritation occurs: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse

**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

**Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do NOT induce vomiting

**Fire**

In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not Applicable

**Unknown Toxicity**

60% of the mixture consists of ingredient(s) of unknown toxicity

**Other information**

- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- Prolonged or repeated contact may dry skin and cause irritation

**Interactions with Other Chemicals**

Irritants. Sensitizers. Epoxies. Use of alcoholic beverages may enhance toxic effects.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name                            | CAS-No    | Weight % | Trade Secret |
|--|-----------|----------|--------------|
| Stoddard solvent                         | 8052-41-3 | 20-55    | *            |
| Aluminum                                 | 7429-90-5 | 5-20     | *            |
| Xylenes (o-, m-, p- isomers)             | 1330-20-7 | 5-20     | *            |
| Hexanoic acid, 2-ethyl-, cobalt(2+) salt | 136-52-7  | 0-4      | *            |

\* The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

#### First aid measures

|                                   |   |
|-----------------------------------|---|
| <b>General Advice</b>             | Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician. Immediate medical attention is required.  |
| <b>Eye Contact</b>                | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. If symptoms persist, call a physician.   |
| <b>Skin Contact</b>               | Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. Consult a physician if necessary. Get medical attention if irritation develops and persists.  |
| <b>Inhalation</b>                 | Move to fresh air. If not breathing, give artificial respiration. Administer oxygen if breathing is difficult and you are trained.  |
| <b>Ingestion</b>                  | Clean mouth with water and afterwards drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs, lean victim forward to reduce the risk of aspiration. Call a physician or Poison Control Center immediately. |
| <b>Protection of First-aiders</b> | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.  |

#### Most important symptoms and effects, both acute and delayed

**Most Important Symptoms/Effects** Coughing and/ or wheezing. Itching.

#### Indication of any immediate medical attention and special treatment needed

**Notes to Physician** May cause sensitization of susceptible persons. Use of epinephrine may be indicated Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Dry chemical, CO<sub>2</sub>, water spray or regular foam. Use water spray or fog; do not use straight streams.

### Unsuitable Extinguishing Media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

### Specific Hazards Arising from the Chemical

Some may be transported hot

|                          |  |
|--------------------------|--|
| <b>Uniform Fire Code</b> | Combustible Liquid: III-A<br>Sensitizer: Liquid<br>Toxic: Liquid |
|--------------------------|--|

|  |                   |
|--|-------------------|
| <b>Physical/Chemical Reaction Properties</b> | No data available |
|--|-------------------|

### Explosion Data

|   |      |
|---|------|
| <b>Sensitivity to Mechanical Impact</b> | None |
|---|------|

|  |     |
|--|-----|
| <b>Sensitivity to Static Discharge</b> | Yes |
|--|-----|

### Protective Equipment and Precautions for Firefighters

Move containers from fire area if you can do it without risk.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

|                             |   |
|-----------------------------|---|
| <b>Personal Precautions</b> | Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment. Keep people away from and upwind of spill/leak. Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists Avoid dust formation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. |
|-----------------------------|---|

|                          |  |
|--------------------------|--|
| <b>Other Information</b> | Water spray may reduce vapor; but may not prevent ignition in closed spaces. |
|--------------------------|--|

### Environmental precautions

|                                  |  |
|----------------------------------|--|
| <b>Environmental Precautions</b> | Prevent entry into waterways, sewers, basements or confined areas. |
|----------------------------------|--|

### Methods and material for containment and cleaning up

|                                |   |
|--------------------------------|---|
| <b>Methods for Containment</b> | A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. |
|--------------------------------|---|

|                                |   |
|--------------------------------|---|
| <b>Methods for Cleaning Up</b> | Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal. |
|--------------------------------|---|

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Do not breathe vapors, mist or gas

### Conditions for safe storage, including any incompatibilities

**Storage** Keep in properly labeled containers. Keep away from heat and sources of ignition. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Store locked up. Protect from moisture. Store away from other materials. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

**Incompatible Products** Strong acids. Strong bases. Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

| Chemical Name                             | ACGIH TLV                                    | OSHA PEL   | NIOSH IDLH  |
|---|--|--|---|
| Stoddard solvent<br>8052-41-3             | TWA: 100 ppm                                 | TWA: 500 ppm<br>TWA: 2900 mg/m <sup>3</sup><br>(vacated) TWA: 100 ppm<br>(vacated) TWA: 525 mg/m <sup>3</sup>  | IDLH: 20000 mg/m <sup>3</sup><br>Ceiling: 1800 mg/m <sup>3</sup> 15 min<br>TWA: 350 mg/m <sup>3</sup> |
| Aluminum<br>7429-90-5                     | TWA: 1 mg/m <sup>3</sup> respirable fraction | TWA: 15 mg/m <sup>3</sup> total dust<br>TWA: 5 mg/m <sup>3</sup> respirable fraction<br>(vacated) TWA: 15 mg/m <sup>3</sup> total dust<br>(vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction | TWA: 10 mg/m <sup>3</sup> total dust<br>TWA: 5 mg/m <sup>3</sup> respirable dust                      |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 | STEL: 150 ppm<br>TWA: 100 ppm                | -  |   |

*Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:*

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Appropriate engineering controls

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems

### Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Tightly fitting safety goggles. Avoid contact with eyes.

**Skin and Body Protection** Wear protective gloves/clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots

**Respiratory Protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene Measures** When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Avoid contact with skin, eyes and clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

|                       |                          |                       |                          |
|-----------------------|--------------------------|-----------------------|--------------------------|
| <b>Physical State</b> | Liquid                   | <b>Odor</b>           | Solvent                  |
| <b>Appearance</b>     | Silver                   | <b>Odor Threshold</b> | No information available |
| <b>Color</b>          | No information available |                       |                          |

| <u>Property</u>                               | <u>Values</u>       | <u>Remarks/ Method</u> |
|---|---------------------|------------------------|
| <b>pH</b>                                     | UNKNOWN             | None known             |
| <b>Melting/freezing point</b>                 | No data available   | None known             |
| <b>Boiling Point/Range</b>                    | 139°C / 282°F       | None known             |
| <b>Flash Point</b>                            | 60C / 140F          | None known             |
| <b>Evaporation rate</b>                       | No data available   | None known             |
| <b>Flammability (solid, gas)</b>              | No data available   | None known             |
| <b>Flammability Limits in Air</b>             |                     |                        |
| <b>Upper flammability limit</b>               | No data available   |                        |
| <b>Lower flammability limit</b>               | No data available   |                        |
| <b>Vapor pressure</b>                         | 3.9 mm Hg @ 20 C    | None known             |
| <b>Vapor density</b>                          | No data available   | None known             |
| <b>Specific Gravity</b>                       | 0.94                | None known             |
| <b>Water Solubility</b>                       | Insoluble in water. | None known             |
| <b>Solubility in other solvents</b>           | No data available   | None known             |
| <b>Partition coefficient: n-octanol/water</b> |                     | None known             |
| <b>Autoignition temperature</b>               | No data available   | None known             |
| <b>Decomposition temperature</b>              | No data available   | None known             |
| <b>Kinematic viscosity</b>                    | No data available   | None known             |
| <b>Dynamic viscosity</b>                      | No data available   | None known             |
| <b>Explosive Properties</b>                   | No data available   |                        |
| <b>Oxidizing Properties</b>                   | No data available   |                        |

### Other Information

|                        |                   |
|------------------------|-------------------|
| <b>Softening Point</b> | No data available |
| <b>VOC Content (%)</b> | No data available |
| <b>Bulk Density</b>    | 7.85 lbs/gal      |

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available.

### Chemical stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to avoid

Heating in air. Excessive heat. Heat, flames and sparks.

### Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

### Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

|                     |   |
|---------------------|---|
| <b>Inhalation</b>   | May cause irritation of respiratory tract. Harmful by inhalation. (based on components). Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.   |
| <b>Eye Contact</b>  | Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain.   |
| <b>Skin Contact</b> | Expected to be an irritant based on components. Irritating to skin. Repeated exposure may cause skin dryness or cracking.   |
| <b>Ingestion</b>    | Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways |

**Component Information**

| Chemical Name                             | LD50 Oral            | LD50 Dermal             | LC50 Inhalation          |
|---|----------------------|-------------------------|--------------------------|
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 | = 4300 mg/kg ( Rat ) | > 2000 mg/kg ( Rabbit ) | = 47635 mg/L ( Rat ) 4 h |

**Information on toxicological effects**

**Symptoms** Redness of the skin. May cause redness and tearing of the eyes. Coughing and/ or wheezing. Difficulty in breathing. Asthma-like and/ or skin allergy-like symptoms.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Mutagenic Effects** Contains a known or suspected mutagen

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical Name   | ACGIH | IARC     | NTP | OSHA |
|---|-------|----------|-----|------|
| Xylenes (o-, m-, p- isomers)<br>1330-20-7               |       | Group 3  |     |      |
| Hexanoic acid, 2-ethyl-,<br>cobalt(2+) salt<br>136-52-7 |       | Group 2B |     | X    |

**IARC: (International Agency for Research on Cancer)**

*Group 2B - Possibly Carcinogenic to Humans*

*Group 3 - Not Classifiable as to Carcinogenicity in Humans*

**OSHA: (Occupational Safety & Health Administration)**

*X - Present*

**Reproductive Toxicity** No information available  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Chronic Toxicity** Avoid repeated exposure. Repeated or prolonged contact causes sensitization, asthma and eczemas. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Contains material which may cause cancer. Contains a known or suspected mutagen. Possible risks of irreversible effects. Contains a known or suspected carcinogen. Aspiration may cause pulmonary edema and pneumonitis.  
**Target Organ Effects** Central nervous system (CNS). Eyes. Kidney. Respiratory system. Skin. May affect the genetic material in germ cells (sperm and eggs). Gastrointestinal tract (GI). Liver. Lungs. Testes  
**Aspiration Hazard** No information available.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document



**ATEmix (oral)**  
8,600.00 mg/kg  
**ATEmix (dermal)**  
2,200.00 mg/kg (ATE)  
**ATEmix (inhalation-gas)**  
9,000.00  
ppm (4 hr)  
**ATEmix (inhalation-dust/mist)**  
3.00 mg/L  
**ATEmix (inhalation-vapor)**  
22.00ATEmix

## 12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT

### Ecotoxicity

Toxic to aquatic life with long lasting effects

### Persistence and Degradability

No information available.

### Bioaccumulation

No information available.

### Other Adverse Effects

No information available.

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Waste Disposal Methods**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

#### **Contaminated Packaging**

Do not re-use empty containers.

#### **US EPA Waste Number**

U239

| Chemical Name                             | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|---|------|--------------------------|------------------------|------------------------|
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 |      |                          |                        | U239                   |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name  | California Hazardous Waste |
|--|----------------------------|
| Aluminum<br>7429-90-5                                | Ignitable powder           |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7            | Toxic<br>Ignitable         |
| Hexanoic acid, 2-ethyl-, cobalt(2+) salt<br>136-52-7 | Toxic                      |

|                                  |
|----------------------------------|
| <b>14. TRANSPORT INFORMATION</b> |
|----------------------------------|

|   |   |
|---|---|
| <b><u>DOT</u></b>                             |   |
| Proper Shipping Name                          | Consumer commodity  |
| Hazard Class                                  | ORM-D   |
| Reportable Quantity (RQ)<br>(RQ/% in mixture) | Xylenes isomers and mixture, RQ kg = 227  |
| Marine Pollutant                              | This product contains a chemical which is listed as a marine pollutant according to DOT |
| Description                                   | Consumer commodity,ORM-D,,RQ  |
| Emergency Response Guide<br>Number            | 128   |
| <br>  |   |
| <b><u>TDG</u></b>                             |   |
| UN-No   | UN1263  |
| Proper Shipping Name                          | Paint   |
| Hazard Class                                  | 3   |
| Packing Group                                 | III   |
| Description                                   | PAINT,3,UN1263,PG III   |
| <br>  |   |
| <b><u>MEX</u></b>                             |   |
| UN-No   | UN1263  |
| Proper Shipping Name                          | Pintura   |
| Hazard Class                                  | 3   |
| Description                                   | UN1263 Pintura,3,   |
| <br>  |   |
| <b><u>ICAO</u></b>                            |   |
| UN-No   | UN1263  |
| Proper Shipping Name                          | Paint   |
| Hazard Class                                  | 3   |
| Packing Group                                 | III   |
| Description                                   | Paint,3,UN1263,PG III   |
| <br>  |   |
| <b><u>IATA</u></b>                            |   |
| UN-No   | UN1263  |
| Proper Shipping Name                          | Paint   |
| Hazard Class                                  | 3   |
| Packing Group                                 | III   |
| Description                                   | UN1263,Paint,3,PG III   |
| <br>  |   |
| <b><u>IMDG/IMO</u></b>                        |   |
| UN-No   | UN1263  |
| Proper Shipping Name                          | Paint   |
| Hazard Class                                  | 3   |
| Packing Group                                 | III   |
| EmS No.                                       | F-E, _S-E_  |
| Description                                   | UN1263, Paint,3,PG III  |
| <br>  |   |
| <b><u>RID</u></b>                             |   |
| UN-No   | UN1263  |
| Proper Shipping Name                          | Paint   |
| Hazard Class                                  | 3   |
| Packing Group                                 | III   |
| Classification Code                           | F1  |
| Description                                   | UN1263 Paint,3,III,RID  |
| ADR/RID-Labels                                | 3   |
| <br>  |   |
| <b><u>ADR</u></b>                             |   |
| UN-No   | UN1263  |

**14. TRANSPORT INFORMATION**

**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**Classification Code** F1  
**Description** UN1263 Paint,3,III,ADR  
**ADR/RID-Labels** 3

**ADN**

UN-No UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**Classification Code** F1  
**Special Provisions** 163, 640E  
**Description** UN1263 Paint,3,III  
**Hazard Labels** 3  
**Limited Quantity** LQ7

**15. REGULATORY INFORMATION****International Inventories**

TSCA Complies  
 DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

| Chemical Name        | CAS-No    | Weight % | SARA 313 - Threshold Values % |
|----------------------|-----------|----------|-------------------------------|
| Aluminum - 7429-90-5 | 7429-90-5 | 5-20     | 1.0                           |

**SARA 311/312 Hazard Categories**

**Acute Health Hazard** Yes  
**Chronic Health Hazard** Yes  
**Fire Hazard** Yes  
**Sudden Release of Pressure Hazard** No  
**Reactive Hazard** No

**Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

**U.S. State Regulations****California Proposition 65**

This product does not contain any Proposition 65 chemicals.

**U.S. State Right-to-Know Regulations**

| Chemical Name  | New Jersey | Massachusetts | Pennsylvania |
|--|------------|---------------|--------------|
| Xylenes (o-, m-, p- isomers)<br>1330-20-7            |            | X             |              |
| Aluminum<br>7429-90-5                                | X          | X             | X            |
| Stoddard solvent<br>8052-41-3                        | X          | X             | X            |
| Hexanoic acid, 2-ethyl-, cobalt(2+) salt<br>136-52-7 |            |               | X            |

**International Regulations****Mexico - Grade**

Moderate risk, Grade 2

| Chemical Name                | Carcinogen Status | Exposure Limits   |
|------------------------------|-------------------|---|
| Stoddard solvent             |                   | Mexico: TWA 100 ppm<br>Mexico: TWA 523 mg/m <sup>3</sup><br>Mexico: STEL 200 ppm<br>Mexico: STEL 1050 mg/m <sup>3</sup> |
| Aluminum                     |                   | Mexico: TWA= 10 mg/m <sup>3</sup>   |
| Xylenes (o-, m-, p- isomers) |                   | Mexico: TWA 100 ppm<br>Mexico: TWA 435 mg/m <sup>3</sup><br>Mexico: STEL 150 ppm<br>Mexico: STEL 655 mg/m <sup>3</sup>  |

**Canada****WHMIS Hazard Class**

B3 Combustible liquid

D2A Very toxic materials

**16. OTHER INFORMATION****NFPA**

Health Hazard 2

Flammability 2

Instability 0

**Physical and Chemical Hazards -****HMIS**

Health Hazard 2 \*

Flammability 2

Physical Hazard 0

**Personal Protection X***Chronic Hazard Star Legend**\*Indicates a chronic health hazard.***Prepared By**Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501**Issuing Date**

27-Apr-2007

**Revision Date**

26-Dec-2013

**Revision Note**

No information available

---

**General Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**